

Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) **EP 1 110 503 A2**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
27.06.2001 Bulletin 2001/26

(51) Int Cl.7: **A61B 5/0402**, A61B 5/044,  
A61B 5/00

(21) Application number: **00311579.7**

(22) Date of filing: **21.12.2000**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE TR**  
Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventors:  
• **Xue, Qiuzhen**  
**Germantown, Wisconsin 53022 (US)**  
• **Reddy, Shankara Bonthu**  
**Cedarburg, Wisconsin 53012 (US)**

(30) Priority: **22.12.1999 US 469824**

(71) Applicant: **GE Marquette Medical Systems, Inc.**  
**Milwaukee, Wisconsin 53223 (US)**

(74) Representative: **Goode, Ian Roy**  
**GE LONDON PATENT OPERATION,**  
**Essex House,**  
**12/13 Essex Street**  
**London WC2R 3AA (GB)**

(54) **Clinical research workstation**

(57) An apparatus and a method for taking multiple physiological signals (e.g., ECG waveforms) from different sources as input, applying multiple algorithms in its core and generating results which are exported for use

in clinical studies and research. The apparatus has a built-in database and a built-in spreadsheet (18) to provide a unified platform for all clinical research in the medical field, including, but not limited to, clinical core laboratory work and high-end clinical research.




FIG.2B

18

## Description

**[0001]** This invention relates to analysis of electrocardio-grams and other physiological data.

**[0002]** Currently there is a lack of tools for physicians and biomedical scientists to do research work with a large amount of physiological data acquired by medical devices. For example, tools do not exist for exporting measurements and waveform data from the original files and evaluating the value of new clinical parameters and algorithms such as QT dispersion, T wave alternans, signal averaging, and heart-rate variability. The currently employed manual methods of extracting measurements and data are laborious and time-consuming and they suffer from high intra- and inter-observer variability and poor reproducibility. A semi-automatic system with options for physician's review and editing would greatly facilitate clinical research work in cardiology and other branches of medicine.

**[0003]** The present invention is directed to an apparatus and a method for taking multiple physiological signals from different sources as input, applying multiple algorithms in its core and generating results which are exported for use in clinical studies and research. The apparatus has a built-in database and a built-in spreadsheet to provide a unified platform for all clinical research in the medical field, including, but not limited to, clinical core laboratory work and high-end clinical research.

**[0004]** The preferred embodiment of the invention is a clinical research workstation capable of handling a wide range of physiological signals including, but not limited to, resting electrocardiogram (ECG), ambulatory ECG, stress ECG, signal-averaged ECG, intra-cardiac electrical and hemodynamic signals, pulse oximetry signals, blood pressure signals, cardiac output signals, electroencephalogram, electro-oculogram, etc. Analysis of each of these physiological signals is supported in one or more separate modules. The research workstation in accordance with the preferred embodiment is also capable of accepting physiological data from a variety of data sources, such as medical devices and systems, including, but not limited to, electrocardiographs, continuous 12-lead ST segment monitors, Holter recorders, stress ECG systems, defibrillators, patient monitors, home healthcare devices, medical data storage/management systems, etc.

**[0005]** In accordance with the preferred embodiment, the research workstation has the capability to export any user-selected data in many output formats and different configurations. Output data will include, but is not limited to, patient demographic information, measurements and waveform signals of both processed and raw data stored in the data file. In addition to the data stored in the file, many measurements and waveforms will also be generated by processing the stored data in the research workstation. Users can select any combination of measurements from a built-in spreadsheet by high-

lighting the ones they need. A batch processing can be used to export the patient demographics, measurements and/or waveform data from the whole directory or a selected database from a built-in Open Database Connectivity (ODBC) database.

**[0006]** With various physiological data as input from multiple data sources, the system will be able to evaluate new parameters using different algorithms. For example, some high-risk cardiac disease indicators such as signal-averaged ECG parameters, QT dispersion, T wave alternans, and heart rate variability, all from the same patient, can be evaluated at the same time. Algorithms which can be optionally built into the research workstation include, but are not limited to, the following: (1) new measurements with and without user-defined re-analysis from physiological data including, but not limited to, resting ECG, ambulatory ECG, stress ECG, intra-cardiac electrical and hemodynamic signals, and ECG, pulse oximetry and blood pressure signals from neo-natal, pediatric and adult patient monitors and defibrillators; (2) interpretation and re-analysis of resting ECG; (3) QT dispersion and T wave alternans; (4) multi-lead vector ECG analysis; (5) signal-averaged ECG processing; (6) ECG mapping and modeling; (7) signal filtering and spectral analysis; and (8) heart-rate variability.

**[0007]** In accordance with a further aspect of the preferred embodiment, the research workstation has a built-in ODBC database (Microsoft Access database). The key parameters are stored automatically into the database, and they can be retrieved, sorted and filtered within the system. With this database, reviewing and editing the measurements and interpretation are very convenient. For example, a few simple operations such as, clicking "go forward" and "go backward" buttons will lead the researcher through physiological data files one by one.

**[0008]** In addition, the system has a built-in spreadsheet for selecting for export, reviewing and plotting any of the measurements. The spreadsheet is compatible with standard data analysis software, including, but not limited to, Microsoft Excel and SAS (statistical analysis software) packages, and can be directly saved as a file compatible with standard data analysis software. Researchers can perform most analysis and plotting inside the system, and the spreadsheet interacts with the built-in database seamlessly. A trend of a selected group of physiological parameters/measurements can also be plotted.

**[0009]** The clinical research workstation provides standard-ized coding/scoring of physiological data, including, but not limited to, Minnesota code, and NOVA-CODE for resting ECG. The research workstation also provides essential functions needed in core laboratories for clinical studies, including, but not limited to, measuring, reviewing and editing of modifiable time markers in physiological waveforms such as waveform onsets, peaks and offsets, re-analysis based on user-modified

markers and serial comparison.

**[0010]** The research workstation software disclosed herein can help physicians advance studies in areas such as disease epidemiology, pharmaceutical research and out-come-based analysis. Using this software, physicians can transform a standard computer with a database program such as Microsoft Access and a spreadsheet program such as Microsoft Excel into an ECG research workstation that allows them to quickly and easily study large volumes of ECG data. The research workstation software enables physicians to store, access, review and plot ECG data with point-and-click efficiency.

**[0011]** An embodiment of the invention will now be described, by way of example, with reference to the accompanying drawings, in which:

**[0012]** FIG. 1 is a block diagram showing a conventional personal computer system which can be programmed with research workstation software.

**[0013]** FIG. 2 is a schematic depicting an ECG research workstation window in accordance with the preferred embodiment of the invention.

**[0014]** FIG. 3 is a schematic depicting a Modify window in accordance with the preferred embodiment of the invention.

**[0015]** FIG. 4 and 5 are schematics depicting a 12SL Statement and an array of selectable parameters for export respectively displayed in spreadsheet format in the Results window in accordance with the preferred embodiment of the invention.

**[0016]** FIG. 6 is a schematic depicting a built-in spreadsheet and chart displayed in the Results window.

**[0017]** FIG. 7 is a schematic depicting a Database window in accordance with the preferred embodiment of the invention.

**[0018]** FIG. 8 is a schematic depicting a "Rest ECG Database Select" window in accordance with the preferred embodiment of the invention.

**[0019]** FIG. 9 is a schematic depicting an "Output ECG files in batch mode" window in accordance with the preferred embodiment of the invention.

**[0020]** The preferred embodiment of the invention comprises research workstation software installed on a computer system. A typical computer system is generally depicted in FIG. 1 and comprises a computer 2, a keyboard 4, a mouse 6, a display monitor 8 and a printer 10. The software of the preferred embodiment requires the following software: an operating system such as Microsoft Windows 95 or 98, or Windows NT 3.51 or 4.0; a database program such as Microsoft Access for Windows; and a spreadsheet program such as Microsoft Excel for Windows. Although the workstation of the invention can be used to perform clinical research on physiological data including, but not limited to, resting ECG, ambulatory ECG, stress ECG, intra-cardiac electrical and hemodynamic signals, and ECG, pulse oximetry and blood pressure signals, the preferred embodiment will be disclosed in the context of ECG signals for the

sake of simplicity, with the understanding that other types of physiological data can be processed in a similar manner. The ECG research workstation incorporates ECG analysis programs such as 12SL from GE Marquette Medical Systems, Inc., which is a computer program for analyzing simultaneously acquired 12-lead ECGs. It makes precise measurements of recorded cardiac signals, then provides an interpretation of the ECG waveforms using ECG interpretation criteria for both rhythm and morphology.

**[0021]** The clinical research workstation software in accordance with the preferred embodiment is used to review and export ECG waveforms, interpretations and measurements for research purposes. The main functions of the research workstation software include: (1) acquiring ECG files from devices and systems; (2) reviewing the ECG waveforms, interpretation and measurements; (3) selecting the ECGs based on user-defined criteria (e.g., age, gender, measurements, interpretation); (4) re-measuring and re-analyzing stored ECGs; and (5) exporting the analysis, measurements and waveform data from the stored ECG files or re-measured/re-analyzed results in a user-selected format.

**[0022]** As used herein, the term "database" includes patient information, parameter data and path names for locating raw ECG (actual waveform) files stored in memory. In addition, the terms "record" and "file" will be used interchangeably.

**[0023]** The terms "class" and "group" will be used interchangeably to refer to groups of records/files in the database.

**[0024]** An ECG research workstation window is presented in FIG. 2, showing the window as it appears on the computer display screen when the computer is running the research workstation software of the preferred embodiment. The title bar 11 contains the title name for the ECG research workstation work area, and the close, maximize and minimize buttons for the ECG research workstation window. As seen in FIG. 2, the window is divided into four quadrants: the upper left-hand quadrant is the Signal window 12, the upper right-hand quadrant is the Modify window 14, the lower left-hand quadrant is the Database window 16, and the lower right-hand quadrant is the Results window 18. The windows can be resized by placing the cursor over the intersection of the window borders or over a horizontal or vertical window border and then dragging the cursor using the mouse 6. The Signal window 12 displays 12-lead ECG data as a standard, median or rhythm strip. The Modify window 14 displays and modifies the appearance of a selected signal from the Signal window 12. The Database window 16 displays the records of the Microsoft Access database. With the Database window active, the user can: (1) perform 12SL re-analysis on a group of ECGs automatically; (2) save the results to the database; and (3) review the data. The Results window 18 displays 12SL results and parameters. The menu bar

20 displays pulldown menu options. The available pulldown menus include File, View, Database, DataSheet, Windows and Help menus. The tool bar 22 provides quick access to commonly used features. The buttons (i.e., tool icons) on the tool bar are available depending upon the function being performed and which window is active. Most of these functions are also available from the pulldown menus. The status bar 24 displays research workstation status information.

**[0025]** The tool bar 22 preferably includes an Open button which opens an ECG file and a Save button which saves the current ECG file. ECG files can also be opened and saved by clicking on Open and Save selections in the File menu.

**[0026]** When an ECG file is opened, the ECG waveforms appear in the signal window 12, a selected one of those displayed wave-forms appears in the Modify window 14, the raw waveform data is processed using the ECG analysis program in accordance with the option selected in the Modify window, and the analysis results are displayed in spreadsheet format in the Results window 18. Major parameters such as patient name, ID, and age appear in the Database window 16 when an ECG file is opened.

**[0027]** As seen in FIG. 2, the Signal window 12 appears in the upper left-hand corner of the ECG research workstation window. It displays the raw, unprocessed waveforms. When the Signal window 12 is active, the ECG signals from an opened ECG file can be displayed in one of three formats, the format being selectable by clicking on a corresponding button on the tool bar menu 22, i.e., the Standard ECG Plot, Median ECGs and Rhythm ECGs buttons. The Standard ECG Plot button displays a standard ECG in the Signal window, which is in the format of 2.5 sec by 4, plus 10 sec of lead II and v.1. The Median ECGs button displays the median beats formed by the ECG analysis program. The Rhythm ECGs button displays the 10-sec 12-lead rhythm ECG in the Signal window.

**[0028]** An individual waveform displayed in the Signal window 12 can be selected for display in the Modify window 14. An individual waveform is selected by clicking on it, or by using the up and down keys on the keyboard 4. Pressing the **PgUp** key selects the first waveform; pressing the **PgDn** key selects the last waveform. A selection bar (not shown), appearing in the form of a vertical line, is used to select a specific point in time on the ECG waveform displayed in the Signal window 12. The selection bar can also be used to take measurements. Whenever the selection bar in the Signal window 12 is moved, data changes in the status bar 24 to reflect the new position. The computerized analysis, measurement and interpretation information is provided by the ECG analysis program.

**[0029]** The Modify window 14 provides individual lead waveform demarcation information and variable display gains, and allows for manual manipulation of automatic demarcation points and complete or partial reanalysis

of the ECG data by the ECG analysis program. The specific lead displayed in this window is selected from the Signal window, as previously described. A Modify window tool bar 26 is displayed directly above the displayed signal, as seen in FIG. 3. The Modify window includes a multiplicity of virtual radio buttons. The radio button 28 (labeled "pon") is used to modify the P onset markers; the radio button 30 (labeled "poff") is used to modify the P offset markers; the radio button 32 (labeled "qon") is used to modify the Q onset markers; the radio button 34 (labeled "qoff") is used to modify the Q offset markers; and the radio button 36 (labeled "toff") is used to modify the T offset marker. These markers appear as green lines on the ECG signal in the Modify window. The procedure for modifying these markers is as follows: (1) in the Modify window tool bar, click on the virtual radio button corresponding to the marker to be modified; and (2) drag the corresponding green line to the desired location.

**[0030]** In addition, the Modify window tool bar can be used to modify the time and/or amplitude resolution for the signal being displayed in the Modify window. One set 38 of virtual radio buttons is provided for changing the time resolution along the X axis; another set 40 of virtual radio buttons is provided for changing the amplitude resolution along the Y axis. The three radio buttons in set 38 correspond respectively to time resolutions of 25, 50 and 100 mm/sec. The three radio buttons in set 40 correspond respectively to amplitude resolutions of 10, 20 and 40 mm/mV. The resolution can be changed by clicking the desired resolution for either the X or Y axis or for both. In response, the signal changes to conform to the new resolutions. The grids in the Modify window do not change size.

**[0031]** Clicking on the Run button 42 runs the ECG analysis program in accordance with a selected one of three options: (1) for the option labeled "meas matrix", only part of the ECG analysis program is performed; (2) for the option labeled "whole 12SL", the whole ECG analysis is performed, generating more than 700 different ECG measurements; and (3) for the option labeled "12SL markers", the ECG analysis program reanalyzes using the modified markers. When an ECG file is opened, the raw ECG data will be automatically processed in accordance with the option previously selected in the Modify window, i.e., without the need to click on the Run button 42. The results of the analysis are automatically displayed as a spreadsheet in the Results window 18. The desired option is selected by clicking on the corresponding virtual radio button in the set 44 in the Modify window tool bar. For example, to run the ECG analysis program with modified markers, the following steps are performed: (1) click in the Modify window to activate it; (2) for each marker to be modified, click on the corresponding radio button in the Modify window tool bar and then drag the corresponding green line to the desired location; (3) select the "12SL Markers" radio button in set 44 in the Modify window tool bar; and (4)

click the Run button 42. The results are displayed in the Results window 18, where they can be reviewed by the researcher.

**[0032]** The Results window 18 appears in the lower right-hand corner of the ECG research workstation window. To view the ECG interpretation statement(s) for the selected patient, the researcher clicks the "12SL Statement" tab 46 in the Results window. The statement and its corresponding code are displayed as shown in FIG. 4. When the "IO12SL" tab 48 is activated, the Results window displays the measurements from resting ECGs and patient file parameters for exporting. The data display format can be selected either via buttons on the tool bar 22 or via items listed on a DataSheet menu (not shown in the drawings). Selection of Sheet on the DataSheet menu displays the exported parameters file as a spreadsheet in the Results window 18. Selection of Chart on the DataSheet menu displays the parameter data in the form of a chart. The Results window can also be used to select parameters for export. In the export parameters mode, the Results window 18 displays an array of selectable parameters, including an array of individual lead amplitudes and durations corresponding to the waveforms displayed in the Signal window 12. To view the window shown in FIG. 5, the user clicks on Select Parameters in the DataSheet menu or a corresponding button in the tool bar 22. This allows the user to select parameters to store in an external file by clicking on the desired parameters. The selected parameters are highlighted. In the example shown in FIG. 5, the selected parameter is indicated by the surrounding rectangular box 52. In response to clicking on Done Parameters Selection! in the DataSheet menu, a dialog box (not shown) appears on the display, asking the user whether the parameters should be exported now. The user clicks Yes to save the file. Then a Save As dialog box (not shown) appears. The user then selects the appropriate directory location and types in the file name. The user then clicks Save to save the file. A Select ECG Source box (not shown) appears having two virtual radio buttons, one labeled "From whole directory" and the other labeled "From ECG database". Selecting "From whole directory" will extract the ECG parameters from all folders in a selected directory. Selecting "From ECG database" will extract the ECG parameters from a selected database class. The ECG parameters are saved when an OK button in the Select ECG Source is clicked on. The exported parameters file can be viewed through the Selection Paras tab 50 in the Results window, e.g., in response to selection of Read Parameters in the DataSheet menu.

**[0033]** In addition, parameters can be viewed in chart form by linking the spreadsheet data to a chart. The procedure for viewing parameters in chart form is as follows: (1) highlight the region in the Results window which is to be linked to a chart; (2) select Link Chart to Sheet on the DataSheet menu to toggle the linkage between the chart values and the chart on; and (3) select

Chart on the DataSheet menu to toggle the chart display on. The selected data appears in chart form in the Results window 18, as shown by representative chart 54 in FIG. 6.

**[0034]** The Database window 16 appears in the lower left-hand corner of the ECG research workstation window. As shown in FIG. 7, the Database window displays information contained in the database. As previously noted, the database includes the path names to raw ECG data files, not the actual waveforms themselves. In accordance with the preferred embodiment of the invention, the Database window comprises the following fields:

- Group: Used to categorize ECGs in the database.
- File: Path to the directory storing the raw ECG file.
- Name: Patient name.
- ID: Patient identification number.
- Age: Patient age.
- Sex: Patient gender.
- Record time: Time the ECG was taken.
- Under the frame labeled "Statement code":
  - ◆ 12SL: ECG interpretation statement codes.
  - ◆ CSE: Special coding, Minnesota coding.
- Under the frame labeled "Global measurements":
  - ◆ Vrate: Ventricular rate.
  - ◆ PRint: PR interval.
  - ◆ qrsd: QRS duration.
  - ◆ Pdur: P duration.
  - ◆ P-R-T axes: P, R and T axes.
  - ◆ QTint: QT interval.
- Under the frame labeled "QT dispersions":
  - ◆ QT-end: from the beginning of the Q wave to the end of the T wave.
  - ◆ QT-peak: from the beginning of the Q wave to the peak of the T wave.
  - ◆ PCAS2: Use principal component analysis to describe T wave morphology.
  - ◆ Leads: Number of leads
- Total records: The number of records used in calculating QT dispersion.
- Current record: The order number of the current record in the database.

**[0035]** To display a specific record in the Signal window, the user must enter the number of the record in the field next to the GOTO button 56 (see FIG. 4). Initially, the record having number 1 is displayed. Thereafter the system user can scroll through the records of the particular database group identified in the Group field by clicking on a Next Record button in the tool bar 22 (see FIG. 1). The toolbar also includes buttons for adding,

deleting and modifying records in the database. During scrolling, the data in all of the windows changes to correspond to the new record, i.e., the waveforms for the next record are displayed in the Signal window, a selected one of those displayed waveforms is displayed in the Modify window, the computed parameters for those displayed waveforms are displayed in the Results window, and the patient information, Statement code, Global measurements and QT dispersions data fields in the Database window are updated. As used herein, the term "global" means that they are measured across all leads. The QT dispersion can be automatically calculated by the computer using any well-known algorithm, such as the algorithms disclosed in U.S. Patent No. 5,792,065 and in the article by Xue *et al.* entitled "Algorithms for Computerized QT Analysis," J. Electrocardiology, Vol. 30 Supplement.

**[0036]** The database tool bar is located in the left side of the tool bar 22. The buttons of the database tool bar are available only when the Database window is active. The database tool bar includes buttons for: displaying a record of the database; adding a record to the end of the database; deleting a record from the database; replacing a current record with a modified version. In addition, the database tool bar has buttons for saving files in a whole directory to a database; performing a database search; batch exporting of patient information and/or ECG data; and batch exporting selected parameters to an external file from a selected database. When the database tool bar is active, its buttons are green. In addition, a Database menu is provided having selections corresponding to the four functions (respectively named Read Files to Database, Select Database, Export Data and Export Parameters) set forth in the next preceding sentence of this paragraph.

**[0037]** When the Database window is active, any group of database records can be loaded in working memory and reviewed by the user. Alternatively, the user may construct a new database group by defining a set of search parameters and then filtering out all data lying outside those parameters. Querying the database is useful in finding ECGs that match certain criteria. A search for data satisfying these conditions can be performed as follows: (1) Click inside the Database window to activate it. (2) Click Select Database from the Database menu. The Rest ECG Database Select window (shown in FIG. 8) appears. This window is used when searching the database for records matching specified criteria. (3) If desired, select a database class from the popup menu. If this field is left blank, then all database records are available for the search. (4) Define the parameters for the ECGs that are sought. There are five filters in the Filters section of the Rest ECG Database Select window. Filter 1 is used if the searcher wants to find a record for a specific patient by name or patient identification number. The remaining filters can be used to set search parameters, e.g., the searcher can search for all ECGs in which the ventricular heart rate is less

than 100 and the QRS duration is less than 120 msec. (5) Then the date and time are entered. (6) If sorting of the data is desired, a sorting methodology can be selected from the Sorting popup menu. For example, the data gathered by the search can be sorted according to Patient ID. (7) Click the OK button. The selected records from the database are loaded in working memory and appear in the Database window. The raw ECG waveforms from the first record in the group are displayed in the Signal window; a selected one of those waveforms is displayed in the Modify window; and the parameters generated by the ECG analysis program are displayed in the Results window.

**[0038]** The preferred embodiment also provides for the batch exportation of data using the following procedure: (1) Click inside the Database window to activate it. (2) Click Export Data from the Database menu. The "Output ECG files in batch mode" window (shown in FIG. 9) appears. (3) The user then selects which data he/she wants to export. The selection of "Patient info" will result in the inclusion of patient information, measurements and parameters for the raw ECG files being output. The raw ECG data to be included in the batch can be either median or rhythm ECG signal, depending on which of the corresponding radio buttons is selected. (4) The user then selects whether the data type will be binary data or text. (5) When the user clicks on the OK button in the "Output ECG files in batch mode" window, the Select ECG Source window (previously described) appears. (6) The user selects where the data is to be retrieved from. Selecting "From whole directory" will extract the data from all folders in a selected directory. Selecting "From ECG database" will extract the data from a selected database class. The ECG parameters are saved when an OK button in the Select ECG Source is clicked on.

**[0039]** ECG files may be imported into the workstation by any conventional means, including but not limited to copying ECG files from a diskette, transferring ECG files from a PCMCIA card via local and wide area networks, wireless communication channels, and internet.

**[0040]** For completeness, various aspects of the invention are set out in the following numbered clauses:

1. A system comprising a computer (2), a display screen connected to said computer (8), and an operator interface (4, 6) connected to said computer, wherein said computer is programmed to perform the following steps:

retrieving raw ECG data from computer memory in response to a retrieve raw ECG data instruction input via said operator interface, said raw ECG data representing a plurality of ECG waveforms; and

following said retrieving step, controlling said display screen to concurrently display first and

second windows, said first window (12) displaying said plurality of ECG waveforms, and said second window (14) displaying an ECG waveform selected from said plurality of ECG waveforms.

2. The system as recited in clause 1, wherein said second window displays a first marker which intersects said ECG waveform in said second window.

3. The system as recited in clause 2, wherein said computer is programmed to control said display screen to displace said first marker in dependence on a move marker instruction input via said operator interface.

4. The system as recited in clause 3, wherein said move marker instruction comprises the steps of placing a cursor over said marker in said second window, activating said cursor and moving said cursor to a new position, said computer being programmed to drag said marker along with said moving cursor when said cursor is active.

5. The system as recited in clause 1, wherein said second window displays a plurality of markers which intersect said ECG waveform in said second window.

6. The system as recited in clause 5, wherein said computer controls said display screen to displace a selected marker of said plurality of markers in response to a marker selection and in dependence on a move marker instruction input via said operator interface.

7. The system as recited in clause 6, wherein said second window comprises a plurality of virtual marker buttons (28-36) corresponding to said plurality of markers, said marker selection comprising the step of clicking on one of said virtual marker buttons corresponding to said selected marker, and said move marker instruction comprises the steps of placing a cursor over said selected marker in said second window, activating said cursor and moving said cursor to a new position, said computer being programmed to drag said selected marker to said new position when said moving cursor is active.

8. The system as recited in clause 7, wherein said second window further comprises a plurality of marker position data fields respectively displayed in close proximity to said plurality of virtual marker buttons, said computer being programmed to display in said plurality of marker position data fields respective numerical values representing the relative positions of said markers in said second window.

9. The system as recited in clause 1, wherein said second window comprises a plurality of virtual ECG analysis option buttons (44) corresponding to a respective plurality of ECG analysis options and a virtual Run button (42), said computer being programmed to run at least a portion of an ECG analysis program on the waveform displayed in said second window in accordance with an ECG analysis option selected by clicking on one of said virtual ECG analysis buttons and in response to clicking on said virtual Run button, said clicking operations being performed via said operator interface.

10. The system as recited in clause 7, wherein said second window comprises a plurality of virtual ECG analysis option buttons (44) corresponding to a respective plurality of ECG analysis options and a virtual Run button (42), said plurality of ECG analysis options including an analysis with modified markers option, said computer being programmed to run an ECG analysis program on the waveform displayed in said second window in accordance with said plurality of markers as modified in response to clicking on the virtual ECG analysis option button corresponding to said analysis with modified markers option followed by clicking on said virtual Run button, said clicking operations being performed via said operator interface.

11. The system as recited in clause 9, wherein said computer is programmed to control said display screen to display a third window (18) concurrently with said first and second windows, said third window displaying a set of parameter values in spreadsheet format if a parameter spreadsheet selection was previously inputted via said operator interface, said parameters being derived by said ECG analysis program from said plurality of ECG waveforms in said first window in accordance with the ECG analysis option selected in said second window.

12. The system as recited in clause 10, wherein said computer is programmed to control said display screen to display a third window (18) concurrently with said first and second windows, said third window displaying an array of parameter values in spreadsheet format if a parameter spreadsheet selection was previously inputted via said operator interface, said parameter values being derived by said ECG analysis program from said plurality of ECG waveforms in said first window in accordance with the modified markers in said second window.

13. The system as recited in clause 1, wherein said computer is programmed to control said display screen to display a third window (18) concurrently with said first and second windows, said third window displaying an array of parameter values in

spreadsheet format if a parameter spreadsheet selection was previously inputted via said operator interface, said parameter values being derived by an ECG analysis program from data representing said plurality of ECG waveforms in said first window.

14. The system as recited in clause 1, wherein said computer is programmed to control said display screen to display a third window (18) concurrently with said first and second windows, said third window displaying a list of ECG analysis statements if an ECG analysis statement selection was previously inputted via said operator interface, said statement being derived by an ECG analysis program from data representing said plurality of ECG waveforms in said first window.

15. The system as recited in clause 13, wherein said third window displays an array of parameter identifiers in said spreadsheet format in response to input of a select parameter instruction via said operator interface, said parameter identifiers corresponding to the parameter values displayed in said array of parameter values.

16. The system as recited in clause 15, wherein said computer is programmed to export selected parameter values from said array of parameter values in response to an export parameters instruction input and in dependence on an export set of parameter identifiers selected via said operator interface.

17. The system as recited in clause 11, wherein said third window displays a chart (54) overlying at least a portion of said spreadsheet in response to input of a display chart instruction via said operator interface, said chart comprising graphical data derived from at least some of said parameter values.

18. The system as recited in clause 1, wherein said second window comprises a plurality of virtual time resolution buttons (38) corresponding to a corresponding plurality of different time resolutions, said computer being programmed to control said display screen to display said selected ECG waveform in accordance with a time resolution corresponding to one of said plurality of virtual time resolution buttons selected via said operator interface.

19. The system as recited in clause 1, wherein said second window comprises a plurality of virtual amplitude resolution buttons (40) corresponding to a corresponding plurality of different amplitude resolutions, said computer being programmed to control said display screen to display said selected ECG waveform in accordance with an amplitude resolution corresponding to one of said plurality of virtual amplitude resolution buttons selected via said op-

erator interface.

20. A system comprising a computer (2), a display screen (8) connected to said computer, and an operator interface (4, 6) connected to said computer, said computer comprising memory for storing a multiplicity of raw ECG files and a database comprising a respective record for each of said raw ECG files, each raw ECG file comprising data representing a plurality of ECG waveforms, and each record comprising a patient identifier, a pathname to the corresponding raw ECG file, and parameter values characteristic of said waveforms of said corresponding raw ECG file, wherein said computer is programmed to perform the following steps:

loading a multiplicity of database records in working memory in response to activation of a load database records function via said operator interface; and

controlling said display screen to concurrently display first and second windows, said first window (12) displaying a plurality of ECG waveforms from a raw ECG file identified by a pathname in one of said loaded database records, and said second window (18) displaying an array of parameter values from said one database record in a spreadsheet format.

21. The system as recited in clause 20, wherein said computer is programmed to control said display screen to change said second window to display a list of ECG analysis statements in response to input of an ECG analysis statement selection via said operator interface, said statement being derived by said ECG analysis program from said plurality of ECG waveforms in said first window.

22. The system as recited in clause 20, wherein said computer is programmed to control said display screen to change said second window to display an array of parameter identifiers in said spreadsheet format in response to input of a select parameter instruction via said operator interface, said parameter identifiers corresponding to the parameter values displayed in said array of parameter values.

23. The system as recited in clause 22, wherein said computer is programmed to export selected parameter values from said array of parameter values in response to an export parameters instruction input and in dependence on an export set of parameter identifiers selected via said operator interface.

24. The system as recited in clause 20, wherein said computer is programmed to control said display screen to change said second window to display a



chart (54) overlying at least a portion of said spreadsheet in response to input of a display chart instruction via said operator interface, said chart comprising graphical data derived from at least some of said parameter values.

5

25. A research workstation comprising:

a display screen (8);

10

an operator interface (4, 6);

memory (2) for storing raw ECG data representing a plurality of ECG waveforms;

15

means (2) for retrieving said raw ECG data from memory in response to a retrieve raw ECG data instruction input via said operator interface; and

means (2) for concurrently displaying said plurality of ECG waveforms in a first window (12) and an ECG waveform selected from said plurality of ECG waveforms in a second window (14) on said display screen.

20

26. The workstation as recited in clause 25, further comprising:

means (2) for displaying a marker on said second window which intersects said selected ECG waveform; and

30

means (2) for changing the position of said marker in response to modify marker instructions input via said operator interface.

35

27. The workstation as recited in clause 25, further comprising means (2) for analyzing said ECG waveforms displayed in said first window, said analyzing means generating a multiplicity of parameter values.

40

28. The workstation as recited in clause 27, further comprising means (2) for displaying said parameters in a spreadsheet format in a third window (18) concurrently with said first and second windows.

45

29. A research workstation comprising:

a display screen (8);

50

an operator interface (4, 6);

memory (2) for storing raw ECG data representing a plurality of ECG waveforms;

55

means (2) for retrieving said raw ECG data from memory in response to a retrieve raw ECG data

instruction input via said operator interface;

means (2) for analyzing said raw ECG data to generate a multiplicity of parameter values; and

means (2) for concurrently displaying said plurality of ECG waveforms in a first window and said multiplicity of parameter values in spreadsheet format in a second window on said display screen.

30. The workstation as recited in clause 29, further comprising means (2) for displaying an array of parameter identifiers in said spreadsheet format in said second window instead of said multiplicity of parameter values, said parameter identifiers corresponding to the parameter values.

31. The workstation as recited in clause 30, further comprising means (2) for exporting selected parameter values from said array of parameter values in response to an export parameters instruction input and in dependence on an export set of parameter identifiers selected via said operator interface.

32. The workstation as recited in clause 29, further comprising means (2) for displaying a chart (54) overlying at least a portion of said spreadsheet in response to input of a display chart instruction via said operator interface, said chart comprising graphical data derived from at least some of said parameter values.

33. A method comprising the steps of:

storing raw ECG data representing a plurality of ECG waveforms;

retrieving said raw ECG data from storage;

displaying one of said plurality of ECG waveforms with a plurality of markers intersecting said displayed ECG waveform;

moving at least one of said displayed markers relative to said displayed ECG waveform; and

analyzing said retrieved raw ECG data using said markers as modified by said moving step to generate a multiplicity of parameter values.

34. A system comprising:

a display screen (8);

an operator interface (4, 6);

memory (2) for storing raw ECG data repre-

senting an ECG waveform;

means (2) for retrieving said raw ECG data from storage in response to a retrieve raw ECG data instruction input via said operator interface; 5

means (2) for displaying said ECG waveform in a window on said display screen with a plurality of markers intersecting said displayed ECG waveform; 10

means (2) for moving at least one of said displayed markers relative to said displayed ECG waveform in dependence on marker movement directions input via said operator interface; and 15

processing means (2) for analyzing said retrieved raw ECG data using said markers as modified by said moving means to generate a multiplicity of parameter values. 20

35. A system comprising a computer (2), a display screen (8) connected to said computer, and an operator interface (4, 6) connected to said computer, wherein said computer is programmed to perform the following steps: 25

retrieving raw ECG data from computer memory in response to a retrieve raw ECG data instruction input via said operator interface, said raw ECG data representing an ECG waveform; 30

following said retrieving step, controlling said display screen to display said ECG waveform in a window (14) with a plurality of markers which intersect said ECG waveform; 35

controlling said display screen to displace a selected one or more of said markers in dependence on marker selections and marker movement directions input via said operator interface; and 40

analyzing said selected ECG waveform using said markers as modified to generate a multiplicity of parameter values. 45

36. The system as recited in clause 35, wherein said window also displays a plurality of virtual marker buttons (28-36) corresponding to said plurality of markers, said marker selection comprising the step of clicking on one of said virtual marker buttons corresponding to said selected marker, and said marker movement directions comprising the steps of placing a cursor over said selected marker in said window, activating said cursor and moving said cursor to a new position, said computer being programmed to drag said selected marker to said new 50

position when said moving cursor is active.

37. The system as recited in clause 36, wherein said window further displays a plurality of marker position data fields in respective close proximity to said plurality of virtual marker buttons, said computer being programmed to display in said plurality of marker position data fields respective numerical values representing the relative positions of said markers in said window.

38. The system as recited in clause 35, wherein said window further displays a plurality of virtual time resolution buttons (38) corresponding to a corresponding plurality of different time resolutions, said computer being programmed to control said display screen to display said selected ECG waveform in accordance with a time resolution corresponding to one of said plurality of virtual time resolution buttons selected via said operator interface.

39. The system as recited in clause 35, wherein said second window further displays a plurality of virtual amplitude resolution buttons (40) corresponding to a corresponding plurality of different amplitude resolutions, said computer being programmed to control said display screen to display said selected ECG waveform in accordance with an amplitude resolution corresponding to one of said plurality of virtual amplitude resolution buttons selected via said operator interface.

## Claims

1. A system comprising a computer (2), a display screen connected to said computer (8), and an operator interface (4, 6) connected to said computer, wherein said computer is programmed to perform the following steps:

retrieving raw ECG data from computer memory in response to a retrieve raw ECG data instruction input via said operator interface, said raw ECG data representing a plurality of ECG waveforms; and

following said retrieving step, controlling said display screen to concurrently display first and second windows, said first window (12) displaying said plurality of ECG waveforms, and said second window (14) displaying an ECG waveform selected from said plurality of ECG waveforms.

2. The system as recited in claim 1, wherein said second window displays at least one marker which intersects said ECG waveform in said second win-

dow.

3. The system as recited in claim 1, wherein said computer is programmed to control said display screen to display a third window (18) concurrently with said first and second windows, said third window displaying a list of ECG analysis statements if an ECG analysis statement selection was previously inputted via said operator interface, said statement being derived by an ECG analysis program from data representing said plurality of ECG waveforms in said first window.

4. A system comprising a computer (2), a display screen (8) connected to said computer, and an operator interface (4, 6) connected to said computer, said computer comprising memory for storing a multiplicity of raw ECG files and a database comprising a respective record for each of said raw ECG files, each raw ECG file comprising data representing a plurality of ECG waveforms, and each record comprising a patient identifier, a pathname to the corresponding raw ECG file, and parameter values characteristic of said waveforms of said corresponding raw ECG file, wherein said computer is programmed to perform the following steps:

loading a multiplicity of database records in working memory in response to activation of a load database records function via said operator interface; and

controlling said display screen to concurrently display first and second windows, said first window (12) displaying a plurality of ECG waveforms from a raw ECG file identified by a pathname in one of said loaded database records, and said second window (18) displaying an array of parameter values from said one database record in a spreadsheet format.

5. A research workstation comprising:

a display screen (8);

an operator interface (4, 6);

memory (2) for storing raw ECG data representing a plurality of ECG waveforms;

means (2) for retrieving said raw ECG data from memory in response to a retrieve raw ECG data instruction input via said operator interface; and

means (2) for concurrently displaying said plurality of ECG waveforms in a first window (12) and an ECG waveform selected from said plurality of ECG waveforms in a second window

(14) on said display screen.

6. The workstation as recited in claim 5, further comprising:

means (2) for displaying a marker on said second window which intersects said selected ECG waveform; and

means (2) for changing the position of said marker in response to modify marker instructions input via said operator interface.

7. A research workstation comprising:

a display screen (8);

an operator interface (4, 6);

memory (2) for storing raw ECG data representing a plurality of ECG waveforms;

means (2) for retrieving said raw ECG data from memory in response to a retrieve raw ECG data instruction input via said operator interface;

means (2) for analyzing said raw ECG data to generate a multiplicity of parameter values; and

means (2) for concurrently displaying said plurality of ECG waveforms in a first window and said multiplicity of parameter values in spreadsheet format in a second window on said display screen.

8. A method comprising the steps of:

storing raw ECG data representing a plurality of ECG waveforms;

retrieving said raw ECG data from storage;

displaying one of said plurality of ECG waveforms with a plurality of markers intersecting said displayed ECG waveform;

moving at least one of said displayed markers relative to said displayed ECG waveform; and

analyzing said retrieved raw ECG data using said markers as modified by said moving step to generate a multiplicity of parameter values.

9. A system comprising:

a display screen (8);

an operator interface (4, 6);

memory (2) for storing raw ECG data representing an ECG waveform;

means (2) for retrieving said raw ECG data from storage in response to a retrieve raw ECG data instruction input via said operator interface; 5

means (2) for displaying said ECG waveform in a window on said display screen with a plurality of markers intersecting said displayed ECG waveform; 10

means (2) for moving at least one of said displayed markers relative to said displayed ECG waveform in dependence on marker movement directions input via said operator interface; and 15

processing means (2) for analyzing said retrieved raw ECG data using said markers as modified by said moving means to generate a multiplicity of parameter values. 20

10. A system comprising a computer (2), a display screen (8) connected to said computer, and an operator interface (4, 6) connected to said computer, wherein said computer is programmed to perform the following steps: 25

retrieving raw ECG data from computer memory in response to a retrieve raw ECG data instruction input via said operator interface, said raw ECG data representing an ECG waveform; 30

following said retrieving step, controlling said display screen to display said ECG waveform in a window (14) with a plurality of markers which intersect said ECG waveform; 35

controlling said display screen to displace a selected one or more of said markers in dependence on marker selections and marker movement directions input via said operator interface; and 40

analyzing said selected ECG waveform using said markers as modified to generate a multiplicity of parameter values. 45

50

55




FIG.1




FIG.9




FIG.2A

FIG.2A

FIG.2B

FIG.2




FIG.2B




FIG.3






FIG. 4

18

A2											
A	B	C	D	E	F	G	H	I	J	K	
1											
2	Age	Weight	vrate	arate	pr	qrsd	qt				
3											
4	pax	qrsax	tax	pdur	qtc						
5											
6											
7	score	qrstime	qrstype								
8											
9	Arrays of individual lead amplitudes & durations										
10	maxrq	I	II	III	aVR	aVL	aVF	V1	V2	V3	V4
11	pona	I	II	III	aVR	aVL	aVF	V1	V2	V3	V4
12	pq	I	II	III	aVR	aVL	aVF	V1	V2	V3	V4
13	pd	I	II	III	aVR	aVL	aVF	V1	V2	V3	V4
14	ppa	I	II	III	aVR	aVL	aVF	V1	V2	V3	V4
15	ppd	I	II	III	aVR	aVL	aVF	V1	V2	V3	V4
16	qa	I	II	III	aVR	aVL	aVF	V1	V2	V3	V4
17	rq	I	II	III	aVR	aVL	aVF	V1	V2	V3	V4
18	rd	I	II	III	aVR	aVL	aVF	V1	V2	V3	V4
19	sq	I	II	III	aVR	aVL	aVF	V1	V2	V3	V4
20	sd	I	II	III	aVR	aVL	aVF	V1	V2	V3	V4
21	rpa	I	II	III	aVR	aVL	aVF	V1	V2	V3	V4
22	rpd	I	II	III	aVR	aVL	aVF	V1	V2	V3	V4
23	spa	I	II	III	aVR	aVL	aVF	V1	V2	V3	V4
12SL Statement 1012SL Selection paras Sheet 4											

52

50

48

46

FIG.5




FIG.6

56 16

Total records:  current record:

Group:  File:

Name:  ID:

age  sex  record date:

Statement code

12SL:

CSE:

Global measurements

vrate:  print:  qrzd:  pdur:

p\_r\_taxes    qtint

QT\_dispersions

QT<sub>e</sub>  QT<sub>f</sub>  PCA2  leads

◀ ▶

FIG.7

Rest ECG Database Select ✕

DB Class  ▼

Filters

	Fields	Conditions
1	<input type="text" value="NONE"/> ▼	<input type="text"/>
2	<input type="text" value="vrate"/> ▼	<input type="text" value="&lt;100"/>
3	<input type="text" value="Qrsd"/> ▼	<input type="text" value="&lt;120"/>
4	<input type="text" value="NONE"/> ▼	<input type="text"/>
5	<input type="text" value="NONE"/> ▼	<input type="text"/>


Date. Time (Example: 1/30/96 9:35:20 AM)

From:  To:

Sorting

▼

FIG.8



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) **EP 1 110 503 A3**

(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:  
**16.07.2003 Bulletin 2003/29**

(51) Int Cl.7: **A61B 5/0402, A61B 5/044,  
A61B 5/00**

(43) Date of publication A2:  
**27.06.2001 Bulletin 2001/26**

(21) Application number: **00311579.7**

(22) Date of filing: **21.12.2000**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE TR**  
Designated Extension States:  
**AL LT LV MK RO SI**


(72) Inventors:  
• **Xue, Qiuzhen**  
Germantown, Wisconsin 53022 (US)  
• **Reddy, Shankara Bonthu**  
Cedarburg, Wisconsin 53012 (US)

(30) Priority: **22.12.1999 US 469824**

(74) Representative: **Goode, Ian Roy**  
**GE LONDON PATENT OPERATION,**  
Essex House,  
12/13 Essex Street  
London WC2R 3AA (GB)

(54) **Clinical research workstation**

(57) An apparatus and a method for taking multiple physiological signals (e.g., ECG waveforms) from different sources as input, applying multiple algorithms in its core and generating results which are exported for use in clinical studies and research. The apparatus has a built-in database and a built-in spreadsheet (18) to provide a unified platform for all clinical research in the medical field, including, but not limited to, clinical core laboratory work and high-end clinical research.



**FIG. 2B**

18

**EP 1 110 503 A3**



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 00 31 1579

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (In I.C.I.7)
X	US 5 956 013 A (GLEI MATTHEW S ET AL) 21 September 1999 (1999-09-21) * column 2, line 50 - column 5, line 67 * * column 7, line 59 - column 8, line 50; figure 1 *	1,2,5,6, 8-10	A61B5/0402 A61B5/044
X	US 5 189 609 A (TIVIG GERHARD ET AL) 23 February 1993 (1993-02-23) * column 11, line 21 - column 12, line 66; figures 7-10 *	1,2,5 3,7	
A	US 5 724 985 A (LEVIN THOMAS G ET AL) 10 March 1998 (1998-03-10) * column 11, line 1 - line 64; figure 2 * * column 15, line 32 - column 17, line 51; figure 4 * * column 21, line 6 - column 22, line 14; figure 11 *	1,2,5	
P,X	WO 00 62664 A (BRIEN WILLIAM G O ;LLEWELLYN MICHAEL D (GB); MULLARKEY WILLIAM J () 26 October 2000 (2000-10-26) * page 6, line 10 - page 8, line 14 * * page 20, line 28 - page 22, line 27 * * page 42, line 27 - page 43, line 23 * * page 45, line 3 - line 17 * * page 51, line 11 - page 52, line 25 * * page 56, line 18 - page 57, line 7; figures 1,11,17 *	4 7-10	TECHNICAL FIELDS SEARCHED (In I.C.I.7)  A61B G06F
X	US 5 305 202 A (CARON PAUL R ET AL) 19 April 1994 (1994-04-19) * column 11, line 35 - column 12, line 64; figure 4 *	7 8-10	
A			
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 19 May 2003	Examiner Artikis, T
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03.82 (P04C01)



European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 00 31 1579

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	US 4 964 410 A (LEAHEY EDWARD ET AL) 23 October 1990 (1990-10-23) * column 3, line 1 - column 5, line 61; figure 2D *	8-10	
A	US 4 098 267 A (PETERSON RONALD T ET AL) 4 July 1978 (1978-07-04) * column 4, line 13 - column 6, line 64; figures 1,2 *	1,5	
A	US 6 004 276 A (BRINSTER ERIC GREGORY ET AL) 21 December 1999 (1999-12-21) * column 3, line 35 - column 4, line 57 * * column 19, line 61 - column 20, line 46; figure 11 * * column 23, line 26 - column 26, line 20; figures 14A-C * * column 49, line 13 - line 67 * * column 57, line 44 - column 59, line 63 *	4	
A	WO 91 02484 A (BIOMETRAK CORP) 7 March 1991 (1991-03-07) * page 12, paragraph 1 - paragraph 3 * * page 15, paragraph 3 - page 21, paragraph 3; figure 6 *	7	
The present search report has been drawn up for all claims			
Place of search <b>MUNICH</b>		Date of completion of the search <b>19 May 2003</b>	Examiner <b>Artikis, T</b>
<b>CATEGORY OF CITED DOCUMENTS</b> X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03.82 (P04-C01)





European Patent  
Office

Application Number

EP 00 31 1579

### CLAIMS INCURRING FEES

The present European patent application comprised at the time of filing more than ten claims.

- ☐ Only part of the claims have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims and for those claims for which claims fees have been paid, namely claim(s):
- ☐ No claims fees have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims.

### LACK OF UNITY OF INVENTION

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

see sheet B

- ☒ All further search fees have been paid within the fixed time limit. The present European search report has been drawn up for all claims.
- ☐ As all searchable claims could be searched without effort justifying an additional fee, the Search Division did not invite payment of any additional fee.
- ☐ Only part of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the inventions in respect of which search fees have been paid, namely claims:
- ☐ None of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the invention first mentioned in the claims, namely claims:



European Patent  
Office

**LACK OF UNITY OF INVENTION  
SHEET B**

Application Number  
EP 00 31 1579

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

**1. Claims: 1-6**

A system comprising a computer, a display screen and an operator interface. Following an input via the operator interface the computer controls the display to concurrently display data in first and second windows

**1.1. Claims: 1-3,5-6**

A system comprising a computer, which retrieves raw ECG data representing a plurality of ECG waveforms from memory and controls the display to concurrently display in a first window the plurality of ECG waveforms and in a second window an ECG waveform selected from said plurality of ECG waveforms

**1.2. Claim : 4**

A system comprising a computer, which has a memory for storing raw ECG files each representing ECG waveforms and a database with a record for each ECG file. The database records comprise a patient identifier, a pathname to the respective ECG file and parameter values characteristic of the ECG waveforms of the file. The computer loads database records to memory and controls the display to concurrently display the ECG waveforms in a first window and an array of the parameter values in a spreadsheet format in a second window

**2. Claim : 7**

A research workstation comprising a display screen, an operator interface, memory for storing raw ECG data each representing ECG waveforms, means for retrieving said raw ECG data, means for analysing said raw ECG data to generate parameter values and means for controlling the display to concurrently display the plurality of ECG waveforms in a first window and the parameter values in a spreadsheet format in a second window

**3. Claims: 8-10**

System and method for displaying a stored ECG waveform together with a plurality of intersecting markers, moving at least one of said markers relative to the ECG waveform according to directions by the user and analysing the ECG waveform to generate parameter values using the modified markers



European Patent  
Office

**LACK OF UNITY OF INVENTION  
SHEET B**

Application Number  
EP 00 31 1579

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

Please note that all inventions mentioned under item 1, although not necessarily linked by a common inventive concept, could be searched without effort justifying an additional fee.

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 31 1579

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

19-05-2003

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5956013	A	21-09-1999	NONE	
US 5189609	A	23-02-1993	EP 0310699 A1	12-04-1989
			DE 3769994 D1	13-06-1991
			HK 2592 A	10-01-1992
			JP 1118920 A	11-05-1989
			SG 85791 G	22-11-1991
			US 5056059 A	08-10-1991
US 5724985	A	10-03-1998	NONE	
WO 0062664	A	26-10-2000	US 6416471 B1	09-07-2002
			AU 4642300 A	02-11-2000
			CA 2365316 A1	26-10-2000
			EP 1176905 A1	06-02-2002
			JP 2002541893 T	10-12-2002
			WO 0062664 A1	26-10-2000
			US 6454708 B1	24-09-2002
US 5305202	A	19-04-1994	NONE	
US 4964410	A	23-10-1990	NONE	
US 4098267	A	04-07-1978	NONE	
US 6004276	A	21-12-1999	AU 6443698 A	22-09-1998
			WO 9838910 A1	11-09-1998
WO 9102484	A	07-03-1991	US 5020540 A	04-06-1991
			AT 173551 T	15-12-1998
			AU 653318 B2	29-09-1994
			AU 5280190 A	03-04-1991
			CA 2064791 A1	23-02-1991
			DE 69032771 D1	24-12-1998
			DE 69032771 T2	29-07-1999
			EP 0489010 A1	10-06-1992
			JP 5500167 T	21-01-1993
			JP 3138752 B2	26-02-2001
			WO 9102484 A1	07-03-1991

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP03/08553

A. CLASSIFICATION OF SUBJECT MATTER  
Int.Cl<sup>7</sup> A61B5/042

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
Int.Cl<sup>7</sup> A61B5/042

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched  
Jitsuyo Shinan Koho 1922-1996 Toroku Jitsuyo Shinan Koho 1994-2003  
Kokai Jitsuyo Shinan Koho 1971-2003 Jitsuyo Shinan Toroku Koho 1996-2003

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X Y A	JP 2001-212096 A (GE Marquette Medical Systems, Inc.), 07 August, 2001 (07.08.01), Full text; all drawings & EP 1110503 A2	1, 2, 7-9, 11-13, 15 3, 5, 6, 10, 14 4
X Y A	JP 6-327643 A (NEC Corp.), 29 November, 1994 (29.11.94), Full text; all drawings (Family: none)	1, 2, 7, 9, 11-13, 15 3, 5, 6, 8, 10, 14 4
X Y A	JP 6-205751 A (Satoko SATO), 26 July, 1994 (26.07.94), Full text; all drawings (Family: none)	1-3, 7, 8, 9, 11-13, 15 5, 6, 10, 14 4

☒ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

\* Special categories of cited documents:  
"A" document defining the general state of the art which is not considered to be of particular relevance  
"E" earlier document but published on or after the international filing date  
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)  
"O" document referring to an oral disclosure, use, exhibition or other means  
"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention  
"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone  
"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art  
"&" document member of the same patent family

Date of the actual completion of the international search  
18 August, 2003 (18.08.03)

Date of mailing of the international search report  
02 September, 2003 (02.09.03)

Name and mailing address of the ISA/  
Japanese Patent Office

Authorized officer

Facsimile No.

Telephone No.

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP03/08553

## C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	JP 2001-8914 A (Dainippon Pharmaceutical Co., Ltd.),	1, 2, 7, 9,
Y	16 January, 2001 (16.01.01),	11-13, 15
A	Full text; all drawings	3, 5, 6, 8, 10,
	(Family: none)	14
		4
Y	JP 63-240830 A (Toho Denshi Kabushiki Kaisha),	9
	06 October, 1988 (06.10.88),	
	Page 2, upper left column, line 3 to upper right	
	column, line 8; Figs. 5, 6	
	(Family: none)	
Y	JP 2001-198096 A (Terumo Corp.),	10
	24 July, 2001 (24.07.01),	
	Par. No. [0060]	
	(Family: none)	
Y	JP 55-69896 A (Fujitsu Ltd.),	14
	26 May, 1980 (26.05.80),	
	Page 2, upper right column, line 16 to page 4,	
	upper left column, line 4	
	(Family: none)	